## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

- 1. (Currently Amended) A wind power installation comprising:
- a pylon having a head;
- a winch;
- at least one deflection roller; and roller; and
- at least one cable passage means in the region of the pylon head for passing therethrough a hauling cable from the winch, wherein the winch is mounted <u>on a vehicle outside</u> the pylon at the base of the wind power <u>installation</u>. installation on a vehicle.
- 2. (Previously Presented) A wind power installation as set forth in claim 1, further comprising a pod wherein the cable passage means is in the pod and is configured for passing through the hauling cable from the winch at a base of the wind power installation.
- 3. (Previously Presented) A wind power installation as set forth in claim 1, further comprising a holding arrangement fixedly connected to a foundation, for an additional winch.
- 4. (Currently Amended) A wind power installation as set forth in claim 1, further comprising a second cable passage means disposed above the pylon head and configured to—raise and lower—facilitate raising and lowering components of the wind power installation within the pylon.

Application No. 10/516,570 Reply to Office Action dated August 9, 2007

- 5. (Currently Amended) A wind power installation as set forth in claim 1 wherein the <u>winch-vehicle</u> is arranged at a base of the wind power installation <u>so that the winch is within the pylon of the wind power installation.</u>
- 6. (Currently Amended) A method of fitting/removing components of a wind power installation comprising:

transporting a winch mounted on a transport vehicle to a base of the wind power installation,

laying a hauling cable rom from the winch to at least one deflection roller in a region of a pylon head and further to a component to be fitted/removed,

attaching the hauling cable to the component, and releasing and letting down or pulling up and fixing the component.

- 7. (Previously Presented) A method as set forth in claim 6 further comprising placing a second winch at the base of the wind power installation.
  - 8. (Currently Amended) A wind power installation, comprising:

a pylon;

a base;

a pod; and

means for moving an object with respect to the pod, wherein the means for moving an object with respect to the pod is at least partially contained within the <u>pod</u>, <u>pod</u> and <u>includes a winch mounted on a transport vehicle</u>.

9. (Currently Amended) The wind power installation of claim 8, wherein the means for moving an object with respect to the pod comprises:

a winch;

a cable guide in the pod;

an opening in the pod; and

a cable coupled to the winch, wherein the cable guide is configured to guide the cable and the cable is configured to pass through the opening in the pod.

## 10. (Canceled)

11. (Currently Amended) The wind power installation of claim 9 wherein the means for moving an object with respect to the pod further comprises:

a second opening in the pod and wherein the winch is located outside the pod and the cable is configured to pass through the second opening in the pod.

## 12.-14. (Canceled)

- 15. (Previously Presented) The wind power installation of claim 9 wherein the opening in the pod is in a hub of the pod.
- 16. (Previously Presented) The wind power installation of claim 9 wherein the opening in the pod is a blade mount opening.
- 17. (Previously Presented) The wind power installation of claim 9 wherein the cable guide comprises:

a deflection roller configured to support the cable.

18. (Previously Presented) The wind power installation of claim 9 wherein the means for moving an object with respect to the pod further comprises:

a second cable guide; and

a second opening in the pod.